



# ZEPRO Z 2000

THE NEW GENERATION OF HEAVY LIFTS



The lighter, stronger lift. Easier and faster installation, with unique standard features:

- Easy installation with pre-installed angle sensor suitable for both steel and aluminium platforms
- The easy-service control card is installed in the frame for protection
- The controller connects easily and directly to the control card without a connection card
- The radio module is quick and easy to install directly on the control card.
- Pre-installed electronic autotilt available as an option, or quickly and easily retrofitted
- The lift construction is optimised for weight and axles are designed for longer service life
- New optimised hose routing ensures reliability and extends the service life.
- Ozone-resistant thermos hoses resist wear and extend the service life service life
- The ZEPRO Clearoil Filter is integrated as an option on new orders
- SP3 wear plates protect the platform from ground wear
- ADR EX II & III enable operation with more types/dangerous goods
- New control card holder is easier to install and service

## ACCESSORIES

- Rollstops
- Warning lamps
- Drive-over lock
- Extra controller
- Radio controller



## ZEPRO CLEAROIL FILTER

**The ZEPRO Clearoil Filter enables you to go further without interruption.**

ZEPRO Clearoil Filter collects everything from dirt and contaminants to condensation and prevents the formation of ice particles in cold weather. The oil is kept clean, reducing wear on the hydraulic parts and maintaining system performance.

# ZEPRO Z 2000



## Specifications

Lift heights	1340, 1530 or 1710 mm
Lift platforms	Steel or aluminium
Drive	12 or 24 V
Standard colour	ZEPRO grey, RAL 7024. Other colours available as an option (minimum of five units).
Cylinders	<b>Tilt:</b> double-acting, adjustable <b>Lift:</b> single-acting, double acting – DA
c/c	140 mm
Underrun protection	Three-piece, laterally and longitudinally adjustable.
Models	Z 2000-135/155/175 MA, Z 2000-135/155/175 DA

## Lift platforms

## Lengths

## Widths

Lift platforms	Lengths	Widths
Steel	1500 – 2500 mm	2450, 2490, 2540, 2560, 2580 mm
Aluminium 40 mm flat	1505 - 2505 mm	2450, 2490, 2540, 2560, 2580 mm

## Weights, example

Lift	Z 2000-135 320 kg	Z 2000-155 333 kg	Z 2000-175 349 kg
Steel platform	1700 x 2540 mm 285 kg	2000 x 2540 mm 335 kg	2500 x 2540 mm 411 kg
Aluminium platform	1705 x 2540 mm 161 kg	2005 x 2540 mm 180 kg	2505 x 2540 mm 210 kg

More information about the Z 2000 is available at [zepro.com](http://zepro.com)



Swedish steel combines light weight with high strength



Component guard provides long durability



Manages heavy loads without compromising on safety